

ZN1A-D4/6DTMZ56U

1080p & 5MP IR IP Domes with GXi Video Analytics

■ Specifications

Model		ZN1A-D4DTMZ56U	ZN1A-D6DTMZ56U
Video Analytics (standard)	Analytics Engine	Advanced tracking algorithm with rich library of detection behaviors	
	Detection Zones	40 zones (Multi-segment Polygons and Lines) in total	
	Rules	60 rules in total	
	Tamper Detection	Supported	
Video Analytics (optional)	Detection Behavior	Enter, Exit, Appear, Disappear, Stop, Direction, Dwell filter; Tailgating; Color Filter	
	Logic Rules	Extends standard rules to allow various combinations of the inputs	
	3D Behavior	Perspective Corrected Size and Speed Filters	
	Object Classification	Configured Max./Min. object sizes and Max./Min. speeds	
	People Tracking	Tracks individuals separately among overlapped multiple people	
	Counting	20 counters in total	
	Counting Line	High accuracy people and vehicle counting	
	Counter Report	Generates counter reports based on the counter database	
	Heatmap Report	Shows relative crowd density of the 24 hour period (criterion: midnight)	
	Meta Data	JSON format, Plain XML Format	
Edge Storage	Storage	1x MicroSD memory card slot / microSDHC / microSDXC (card not included)	
Physical	Material	Aluminum Die-Casting; White	
	Language	English	
	IR LEDs	2 Smart IR LEDs (80' Range)	
	Power Source	12VDC, PoE (IEEE 802.3af)	
	Power Consumption	12VDC Max. 7.5W / PoE Max 9.5W	
	Operating Conditions	[12VDC/PoE] -40°F ~ 122°F (-40°C ~ 50°C) / Humidity 10% to 90% RH (non-condensing)	
	Dimensions	5.5" (Ø) x 4.9" / 139mm (Ø) x 125.4mm	
	Weight	2.8 lbs / (1250g)	
	Certifications	FCC, CE, IP67, Onvif S, IP67	

All specifications are subject to change without notice.