



1080p IR IP Mini Dome

ZN8-D4NTFN4L-E



Features:

- 1/2.7" Progressive Scan CMOS
- 3.6mm Lens
- 1080P@30fps
- True Day / Night
- IR Range 49'
- 3D DNR, dWDR
- Supports ROI, Corridor Mode, HLC
- IP66

ZN8-D4NTFN4L-E

1080p IR IP Mini Dome

■ Specifications

Model	ZN8-D4NTFN4L-E
Image Sensor	1 / 2.7" Progressive Scan CMOS
Minimum Illumination	Color 0.2Lux; IR ON 0 Lux
Day / Night Performance	True Day / Night (ICR)
Wide Dynamic Range	Digital WDR
Shutter Speed	1/1-1/10000
Auto Iris	Fixed
Digital Noise Reduction	2D / 3D
Lens	3.6mm Fixed Lens
Field of View	85°
IR LED	12 IR LEDs (49' range)
Max. Resolution	1920x1080 @30fps
Video Compression	H.264 High / Main / Baseline Profile, MJPEG
Bit Rate (CBR / VBR)	Main Stream:500kb-12000kb; Sub Stream 100kb-6000kb
Audio Compression	G.711, RAW_PCM
Stream	Stream1 1920x1080 / 1280x720 Stream 2 D1 to QVGA
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
Network Protocols	IPv4, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, Unicast and Multicast
Alarm Trigger	Motion Detection, Network Disconnect, Disk Alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player
Security	User Security Authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese
System Compatibility	Onvif
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Power Supply	12VDC / PoE
Power Consumption	2.5W / 5W LED On
Operating Temperature	Starting Temperature 14°F ~ 122°F (-10°C ~ 50°C) Working Temperature -4°F ~ 122°F (-20°C ~ 50°C)
Operating Humidity	0% - 90% RH (non-condensing)
Weather Rating	IP66
Dimensions	3.7"(Ø) x 2.5"(H) / 95mm(Ø) x 63mm(H)
Weight	0.6lbs / 280g
Certifications	CE, FCC

All specifications are subject to change without notice.